FATIGUE SAFETY FACTOR TESTING METHOD
AND FATIGUE SAFETY FACTOR TESTING APPARATUS

Background of the Invention

5 ## 1. Field of the Invention

[001]   The present invention relates to a fatigue safety factor testing apparatus and a method of testing a fatigue safety factor, and more particularly to a fatigue safety factor testing apparatus and a

10 method of testing a fatigue safety factor which tests a fatigue safety factor dependent on temperature.

2. Description of the Related Art

[002]   A method of calculating a fatigue safety factor of a part using Computer Aided Engineering

15 (hereinafter, to be referred to as "CAE") is known. A calculation program for this purpose is commercially available in which a fatigue limit diagram is calculated to the part consisting of a kind of material under a predetermined condition, e.g., a

20 predetermined temperature. Here, the fatigue limit diagram is a graph showing relationship between mean stress permissible to an object to be tested and permissible amplitude stress.

[003]   When only the fatigue limit diagram

25 calculated under the predetermined condition can be used, it is difficult to accurately estimate an actual fatigue limit of the part in case of different

conditions, e.g., different temperature depending on the location of the part. A component of an engine of a vehicle such as a piston is exemplified as such a part. In case of the piston, the piston moves in up and down directions in accordance with explosion in an engine cylinder at high speed, and the temperature is different largely depending on a portion of the piston.

[004]   Also, when the fatigue limit of the part can not be estimated precisely, it is not possible to estimate the fatigue safety factor of the part correctly. Therefore, the safety has the first priority and a very high safety factor is set. As a result, this leads the increase of weight of the engine, the increase of material cost and so on, resulting in increase of the environment load. Thus, the technique is demanded that can calculate the fatigue safety factor of each part at high speed and correctly through an automatic process based on the temperature and stress of every portion.

[005]   In conjunction with the above description, a processor for a numerical value simulation of a deformation process of a metal plate is disclosed in Japanese Laid Open Patent Application (JP-A-Heisei 8-339396). This conventional processor has an input section, a rapture limit distortion/wrinkle limit stress data storage section, a rapture/wrinkle margin

calculating section, a rapture/wrinkle margin data
storage section and an output section. The input
section stores distortion/stress data of each element
obtained from the numerical value simulation of a

5 plastic deformation process of the metal plate using a
finite-element method in the distortion/stress data
storage section. The rapture limit distortion/wrinkle
limit stress data storage section stores rapture limit
distortion/wrinkle limit stress data. The

10 rapture/wrinkle margin calculating section calculates
a rapture/ wrinkle margin of each element from the
rapture limit distortion/ wrinkle limit stress data
and distortion/stress data of each element. The
rapture/wrinkle margin data storage section stores the

15 calculated rapture/ wrinkle margin of each element.
Then, the output section outputs a contour line
distribution of the rapture/wrinkle margin.

Summary of the Invention

[006] 20   Therefore, an object of the present invention
is to provide a fatigue safety factor testing
apparatus and a method of testing a fatigue safety
factor, in which the fatigue safety factor of each
part can be calculated at high speed and correctly

25 through an automatic process based on temperature and
stress of every portion of the part which are measured
or calculated.

[007]   Also, another purpose of the present invention is to provide a fatigue safety factor testing apparatus and a method of testing a fatigue safety factor, in which a fatigue limit diagram is 5 calculated which does not depend on material and temperature of a part and a fatigue safety factor of the part can be easily calculated.

[008]   Also, another purpose of the present invention is to provide a fatigue safety factor 10 testing apparatus and a method of testing a fatigue safety factor, in which it is possible to improve the efficiency of design and development, and a cost for them can be reduced.

[009]   In an aspect of the present invention, a 15 fatigue safety factor testing apparatus includes a FEM calculating section, a normalized stress calculating section and a fatigue safety factor calculating section. The FEM calculating section carries out a FEM calculation to meshes of a part to calculate a 20 stress of each of the meshes of the part. The normalized stress calculating section calculates a normalized stress of a stress applied to each of the meshes with respect to a fatigue limit as a function of a temperature and material of each of the meshes. 25 The fatigue safety factor calculating section calculates a fatigue safety factor of each of the meshes based on a normalized fatigue limit obtained by

normalizing the fatigue limit and the normalized stress.

[010]   Here, the normalized stress and the normalized fatigue limit may be independent from the temperature and material of each of the meshes of the part, or may be independent from the temperature of each of the meshes of the part.

[011]   Also, the fatigue safety factor testing apparatus may further include a function table which stores a conversion function as a function of the temperature and the material. The normalized stress calculating section refers to the function table based on the material of each of the meshes of the part to acquire the conversion function, and normalizes the stress applied to each of the meshes of the part using the conversion function. In this case, the fatigue safety factor testing apparatus may further include a stress data table which has the fatigue limit as a function of the material and the temperature, and a conversion function generating section which generates the conversion function based on the fatigue limit for every temperature, and stores the generated conversion function in the function table. In this case, the conversion function generating section may generate the normalized fatigue limit in addition to the conversion function and stores the normalized fatigue limit in the stress data table in relation to the

material. The fatigue safety factor calculating

section may refer to the stress data table based on a

material of each of the meshes of the part to acquire

the normalized fatigue limit.

[012]   5   Also, the fatigue safety factor testing

apparatus may further include a display section which

displays each of the meshes of the part in a color

corresponding to the fatigue safety factor.

[013]   In another aspect of the present invention,

    10 fatigue safety factor testing apparatus include a

normalized stress calculating section and a fatigue

safety factor calculating section. The normalized

stress calculating section normalizes a stress applied

to a part using a conversion function for converting

    15 fatigue limit for every temperature of the part and

for every material of the part into a normalized

fatigue limit which does not depend on the temperature

and outputs as a normalized stress. The fatigue

safety factor calculating section calculates a fatigue

    20 safety factor of the part based on the normalized

fatigue limit and the normalized stress.

[014]   Here, the fatigue safety factor testing

apparatus may further include a function table which

stores the conversion function. The normalized stress

    25 calculating section refers to the function table based

on a material of each of the meshes of the part to

acquire the conversion function. The fatigue safety

factor testing apparatus may further include a stress data table which has the fatigue limit for every temperature and for every material, and a conversion function generating section which generates the

5   conversion function based on the fatigue limit for every temperature and for every material, and stores the generated conversion function in the function table.

[015]   Also, the stress is at least one of mean

10 stress and amplitude stress applied to the part, and the fatigue limit shows a permissible mean stress and a permissive amplitude stress.

[016]   In another aspect of the present invention, a method of testing a fatigue safety factor is achieved

15 by (a) acquiring a stress applied to each of meshes of a part; by (b) normalizing the stress using a conversion function for converting fatigue limit for a material of each of meshes of a part and for every temperature into a normalized fatigue limit which does

20 not depend on the temperature; and by (c) calculating the fatigue safety factor of each of the meshes of the part based on the normalized fatigue limit obtained by normalizing the fatigue limit using the conversion function and the normalized stress.

[017] 25   The method may further include (d) determining the conversion function through the normalization of the fatigue limit;

[018]   Also, the stress may be at least one of mean stress and amplitude stress applied to the part, and the fatigue limit shows a permissible mean stress and a permissive amplitude stress.

[019] 5   Also, the method may further include displaying each of the meshes of the part in a color corresponding to the fatigue safety factor.

[020]   In another aspect of the present invention, a software product executed by a computer and recording
10 codes of a method which is achieved by (a) acquiring a stress applied to each of meshes of a part; by (b) normalizing the stress using a conversion function for converting fatigue limit for a material of each of meshes of a part and for every temperature into a
15 normalized fatigue limit which does not depend on the temperature; and by (c) calculating the fatigue safety factor of each of the meshes of the part based on the normalized fatigue limit obtained by normalizing the fatigue limit using the conversion function and the
20 normalized stress.

[021]   In the software product, the method may further include (d) determining the conversion function through the normalization of the fatigue limit;

[022] 25   Also, the stress is at least one of mean stress and amplitude stress applied to the part, and the fatigue limit shows a permissible mean stress and

a permissive amplitude stress.

[023]   Also, in the software product, the method may further include displaying each of the meshes of the part in a color corresponding to the fatigue safety

5   factor.

Brief Description of the Drawings

[024]   Fig. 1 is a diagram showing the structure of a fatigue safety factor testing apparatus according to

10   an embodiment of the present invention;

[025]   Figs. 2A and 2B are graphs showing examples of a fatigue limit diagram and a normalized fatigue limit diagram obtained;

[026]   Fig. 3 is a diagram showing a method of

15   calculating the fatigue safety factor by using the normalized fatigue limit diagram;

[027]   Fig. 4 is a diagram showing a stress data table;

[028]   Fig. 5 is a diagram showing a function table;

[029] 20   Fig. 6 is a flow chart showing the operation of the fatigue safety factor testing apparatus according to the embodiment of the present invention; and

[030]   Figs. 7A to 7C are diagrams showing the

25   conversion results of tetra mesh data.

Description of the Preferred Embodiments

[031]   Hereinafter, a fatigue safety factor testing apparatus of the present invention will be described with reference to the attached drawings. In the

5 following, the fatigue safety factor testing apparatus used for engine design of a vehicle will be described as an example, but the present invention is not limited to it and is applicable to the design and development of other building and structure.

[032] 10   The structure of the fatigue safety factor testing apparatus according to an embodiment of the present invention will be described with reference to Fig. 1. As shown in Fig. 1, the fatigue safety factor testing apparatus 1 according to the embodiment of the

15 present invention is an information processing apparatus such as a work station and a personal computer. The fatigue safety factor testing apparatus 1 is composed of a CPU 2, a storage section 3 such as a hard disk, a memory 4 such as a RAM, a display

20 section 5, and an input section 6 such as a keyboard and a mouse.

[033]   In the fatigue safety factor testing apparatus 1, the CPU contains of a conversion function generating section 10, a model generating section 11,

25 a condition setting section 12, an FEM calculating section 13, a normalized stress calculating section 14, a fatigue safety factor calculating section 15.

All of them are realized as sections for executing a series of programs stored in the storage section 3.

[034]   Also, the storage section 3 stores a stress data table 17 and a function table 18. The stress data table 17 stores relationship of a kind of material and a fatigue limit diagram indicating relationship between mean stress and amplitude stress. The function table 18 stores relationship of a kind of material and conversion functions for normalizing and converting the fatigue limit diagram to the material every temperature into the normalized fatigue limit diagram independent from temperature and material.

[035]   The conversion function generating section 10 executes a software program and generates a conversion function A and a conversion function B from a fatigue limit diagram for a kind of material stored in the stress data table 17 and stores in the function table 18. The conversion functions A and B are used to generate the normalized fatigue limit diagram.

[036] 20   The model generating section 11 supports the design of a three-dimensional (hereinafter, to be also referred to as "3D") model of an engine as an object of structural analysis. The model generating section 11 is a section for executing a CAD (Computer Aided Design) software program, for example. The conventional CAD software program can be used.

[037]   The condition setting section 12 executes a

software program and sets conditions about the engine

as the object of the structural analysis. The

conditions are used in FEM calculation. The

conditions contain engine operation conditions such as

5 speed, acceleration and torque, and engine

specifications such as a rotation frequency,

horsepower, and a pressure in a cylinder.

[038]   The FEM calculating section 13 converts the

above-mentioned three-dimensional model into an FEM

10 model. Then, the FEM calculating section 13 carries

out FEM calculation for the FEM analysis to the FEM

model under the above conditions. The FEM calculating

section 13 is a section for executing an FEM software

program, for example.

[039] 15   The normalized stress calculating section 14

executes a software program and normalizes the stress

applied to a part by using the fatigue limit diagram

for the material of the part for every temperature of

the part and outputs as a normalized stress. That is,

20 the stress of the fatigue limit diagram corresponds to

the normalized stress of the normalized fatigue limit

diagram.

[040]   The fatigue safety factor calculating section

15 executes a software program and calculates a

25 fatigue safety factor of the part based on the

normalized fatigue limit diagram and the normalized

stress calculated by the normalized stress calculating

section 14.

[041]   The fatigue limit diagram and the normalized fatigue limit diagram used in the fatigue safety factor testing apparatus of the present invention will

5   be described. Figs. 2A and 2B are graphs showing examples of a fatigue limit diagram of some material and a normalized fatigue limit diagram obtained by normalizing it. Fig. 2A shows a fatigue limit diagram and Fig. 2B shows the normalized fatigue limit

10 diagram.

[042]   In the fatigue limit diagram shown in Fig. 2A, the horizontal axis is mean stress $\sigma 1$ and the vertical axis shows amplitude stress $\sigma 2$. A curve Q_1 (point a_1 - point b1 - point e_1 - point c_1 - point d_1),

15 a curve Q_2 (Point a_2 - point b_2 - point e_2 - point c_2 - point d_2), and a curve Q_3 (point a_3 - point b_3 - point e_3 - point c_3 - point d_3) are the fatigue limit diagram at the room temperature, 100 °C, and 200 °C, respectively. The fatigue limit diagram is a graph

20 showing a value of the fatigue limit every temperature, and is generally determined depending on the material but the profile is different. Fig. 2A is only an example. Also, in the temperature range in which the engine is used, the profile becomes small in

25 size similarly with the increase of the temperature (the curve Q_1 to the curve Q_2, to the curve Q_3).

[043]   The calculation of the fatigue limit diagram

is complicated because the profile depends on the material and the temperature. Therefore, in the present invention, the normalized fatigue limit diagram as shown in Fig. 2B is introduced. The

5   normalized fatigue limit diagram is obtained by normalizing mean stress and amplitude stress σ2 by using the fatigue limits in the temperature. In the normalized fatigue limit diagram, the horizontal axis is normalized mean stress σU1 obtained by normalizing

10 the mean stress σ1, and the vertical axis is normalized amplitude stress σU2 obtained by normalizing the amplitude stress σ2. The curves Q_1 to Q_3 of the fatigue limit diagram are all converted into a curve Q_0. That is, the points a_1 to a_3 of the curves

15 Q_1 to Q_3 are converted into the point $a_0(-1, 0)$. The points b_1 to b_3 are converted into the point $b_0(-1, 1)$. The points e_1 to e_3 are converted into the point $e_0(0, 1)$. The points c_1 to c_3 are converted into the point $c_0(1, 1)$. The points d_1 to d_3 are converted into the

20 point $d_0(1, 0)$. The point P on the fatigue limit diagram in case of T = 24 °C becomes the point P_0 on the normalized fatigue limit diagram. Thus, the normalized fatigue limit diagram does not depend on the material and temperature and becomes the curve Q_0.

[044]   25   In this way, the stress σ is normalized and becomes a dimensionless quantity. The manipulation becomes easy in case of fatigue safety calculation and

calculation using the mean stress and the amplitude stress between different kinds of materials and different temperatures.

[045]   The conversion function f is used for the conversion from the fatigue limit diagram into the normalized fatigue limit diagram. For example, as for the point $P(\sigma1_P, \sigma2_P)$, elements are converted into $\sigma U1_P = f_A(\sigma1_P, T)$ and $\sigma U2_P = f_B(\sigma2_P, T)$, and the point $P(\sigma1_P, \sigma2_P)$ is converted into a point $P_0(\sigma U1_P, \sigma U2_P)$. Because the fatigue limit diagram is not constant and is different depending on a kind of the material and temperature, the material conversion function $f(\sigma, T)(f_A(\sigma1, T), f_B(\sigma2, T))$ is set every kind of material.

[046]   The conversion function f is generated as follows. First, the curve Q and each point P on the fatigue limit diagram are converted into a curve and points on the polar coordinate system. That is, a point $S(\sigma1_0, \sigma2_0)$ on the curve Q and the point $P(\sigma1_P, \sigma2_P)$ on the graph are converted into a point $S(r_0, \theta_0)$ on the polar coordinate system and a point $P(r_P, \theta_P)$ on the polar coordinate system. Here, $\sigma1_{0, P} = r_{0, P} \cdot \cos\theta_{0, P}$, $\sigma2_{0, P} = r_{0, P} \cdot \sin\theta_{0, P}$. Then, the curve Q (point S) on the fatigue limit diagram is converted into the curve Q_0 (point S_0) on the normalized fatigue limit diagram. In this case, θ_0 is not changed just as it is, and a coefficient k to r_0 is determined such that the point S on the curve Q is mapped the point S_0

on the curve Q_0. As a result, the point S is mapped to the point $S_0(k \cdot r_0, \theta_0)$ on the curve Q_0. Then, the point P is mapped into the point $P_0(k \cdot r, \theta)$ on the normalized fatigue limit diagram using the value k.

[047] 5   As known, the fatigue limit diagram becomes small similarly or while keeping the shape as the temperature increases. Therefore, a coefficient q(T) is determined which becomes larger when temperature T becomes higher from a reference temperature T_0 and

10 becomes smaller when temperature T becomes lower from the reference temperature T_0. The coefficient q(T) is determined from the fatigue limit diagram every material. That is, the point $P(\sigma1_P, \sigma2_P)$ is mapped into a point $P_0(q(T) \cdot k \cdot r, q(T) \cdot \theta)$ on the polar

15 coordinate system and the point $P_0(\sigma U1_P, \sigma U2_P)$ in the $\sigma1$-$\sigma2$ coordinate system. From this,

$$\sigma U1_P = f_A(\sigma1_P, T)$$
$$= q(T) \cdot k \cdot r \cdot \cos\theta$$
$$= q(T) \cdot k \cdot (\sigma1^2 + \sigma2^2)^{1/2} \cdot \sigma1 \cdot (\sigma1^2 + \sigma2^2)^{-1/2}$$

20 $$\sigma U2_P = f_B(\sigma2_P, T)$$
$$= q(T) \cdot k \cdot r \cdot \sin\theta$$
$$= q(T) \cdot k \cdot (\sigma1^2 + \sigma2^2)^{1/2} \cdot \sigma2 \cdot (\sigma1^2 + \sigma2^2)^{-1/2}$$

where $r = (\sigma1^2 + \sigma2^2)^{1/2}$

$$\cos\theta = \sigma1 \cdot (\sigma1^2 + \sigma2^2)^{-1/2}$$

25 $$\sin\theta = \sigma2 \cdot (\sigma1^2 + \sigma2^2)^{-1/2}$$

[048]   It should be noted that the conversion function f of the present invention is not limited to

the above example. Any type of conversion function may be used if it is possible to convert the fatigue limit diagram into the graph shown in Fig. 2B.

[049]   Next, the method of calculating the fatigue

5 safety factor using the above-mentioned normalized fatigue limit diagram will be described. Fig. 3 is a diagram showing the method of calculating the fatigue safety factor using the normalized fatigue limit diagram. The normalized fatigue limit diagram shown

10 here is the same as a graph shown in Fig. 2B. In Fig. 3, a fatigue safety factor (Saf) to the point P_0 is a ratio of the distance B from the origin point O to the point P_0 to the distance A from the origin point O of the graph to the point S_0. That is, Saf = A/B. Here,

15 the point S_0 is an intersection point of the straight line OP_0 and the curve Q_0.

[050]   Next, the stress data table 3 will be described. Fig. 4 is a diagram showing the stress data table 3. The stress data table 17 stores

20 relationship of a kind of the material and a fatigue limit diagram showing the relationship between the mean stress and the amplitude stress. The stress data table 17 has fields of material 17-1, temperature 17-2, mean stress 17-3, and amplitude stress 17-4. The

25 material field 17-1 stores a kind of material, and contains a case of different states in the same kind of material. The temperature field 17-2 stores the

temperature of the material. The means stress filed 17-3 and the amplitude stress field 17-4 store relations of the mean stress and the amplitude stress in case of the material in the material field 17-1 and the temperature in the temperature field 17-2. The stress data table 3 shows the graph shown in Fig. 2A. It is not necessary to prepare many temperature data as data in the temperature filed 17-2 for every material. It is sufficient to prepare the temperature data for the temperature of 20 °C, 50 °C and 100 °C. Thus, the number of data to be stored can be restrained.

[051]   Fig. 5 is a diagram showing the function table 18. The function table 18 stores relationship of a kind of the material and the conversion functions. The material field 18-1 is the same as the material field 17-1. The conversion function A 18-2 and the conversion function B 18-3 are functions used to convert or map data on the fatigue limit diagram into the data on the normalized fatigue limit diagram. The conversion function A 18-2 is for mean stress $\sigma 1$ and the conversion function B 18-3 is for amplitude stress $\sigma 2$. The details are already described referring to Figs. 2A and 2B. For example, in the examples shown in Figs. 2A and 2B, the conversion function A 18-2 is $f_A(\sigma 1, T) = q(T) \cdot k \cdot (\sigma 1^2 + \sigma 2^2)^{1/2} \cdot \sigma 1 \cdot (\sigma 1^2 + \sigma 2^2)^{-1/2}$, and the conversion function B 18-3 is

$f_B(\sigma2, T) = q(T) \cdot k \cdot (\sigma1^2 + \sigma2^2)^{1/2} \cdot \sigma2 \cdot (\sigma1^2 + \sigma2^2)^{-1/2}$. It should be noted that the conversion function A 18-2 and the conversion function B 18-3 are generated by the conversion function generating section 10 and are stored in the function table 18. However, they may be previously prepared. In this case, a part of the following calculation process can be omitted.

[052]   Next, an operation of the fatigue safety factor testing apparatus according to the embodiment of the present invention will be described. Fig. 6 is a flow chart showing the operation of the fatigue safety factor testing apparatus according to the embodiment of the present invention.

(1) Step S01

[053] 15   The designer selects a material relating to the CAE analysis. The conversion function generating section 10 generates the conversion function A and the conversion function B for the material based on the stress data base 17 (material 17-1, temperature 17-2, mean stress 17-3 and amplitude stress 17-4 of a fatigue limit diagram) and stores it in the function table 18. That is, the conversion function generating section 10 generates the conversion functions $f_A(\sigma, T)$ and $f_B(\sigma, T)$ which are used to generate a graph shown in Fig. 2B from the graph shown in Fig. 2A and stores them in the function table 18 as the conversion function A and the conversion function B,

respectively. Also, the normalized fatigue limit
diagram obtained at this time may be stored in the
stress data table 17.

(2) Step S02

[054]   5   The designer designs a three-dimensional
model of an engine as an object of the structural
analysis using the model generating section 11.

(3) Step S03

[055]   The designer sets conditions of the engine as
   10   the object of the structural analysis using the
condition setting section 12. The conditions are
operation conditions of the engine and specifications
of the engine, such as rotation frequency, horsepower,
and cylinder internal pressure.

   15   (4) Step S04

[056]   The FEM calculating section 13 converts the
above-mentioned three-dimensional model into a FEM
model. Then, FEM calculation is carried out for the
FEM analysis to the FEM model under the above
   20   conditions. The FEM calculating section 13 carries
out two kinds of analyses A and B.

   A: The temperature of each section of the FEM model
with a tetra mesh structure is calculated.

   B: The stresses such as mean stress and amplitude
   25   stress at each section of the FEM model with the tetra
mesh structure are calculated.

(5) Step S05

[057]   The normalized stress calculating section 14 normalizes each of the stresses of a part of the engine calculated at the step S04. At this time, the fatigue limit diagram and the conversion functions f

5   (the conversion function A 18-2 and the conversion function B 18-3 corresponding to the material 18-1 of the part) stored in the function table 18 for temperature and material of the part are used. When the normalized fatigue limit diagram is stored, the

10   normalized fatigue limit diagram and the conversion functions f may be used. Then, the normalized stress calculating section 14 outputs the conversion result as the normalized stresses.

(6) Step S06

[058] 15   The fatigue safety factor calculating section 15 calculates the fatigue safety factor of the part based on the normalized fatigue limit diagram calculated from the fatigue limit diagram using the conversion functions or stored in the stress data

20   table 17 and the normalized stresses calculated at the step S05 by the method described with reference to Fig. 3. Then, the fatigue safety factor calculating section 15 controls the display section 5 to display each of tetra meshes in the color corresponding to a

25   value of the calculated fatigue safety factor.

[059]   The fatigue safety factor becomes able to be easily calculated by using the normalized fatigue

limit diagram. Also, because each tetra mesh is
displayed in the color corresponding to the fatigue
safety factor, the fatigue safety factor is easy to
grasp as the whole of part. Also, the fatigue safety
5   factor becomes able to be grasped visually and
objectively.

[060]   Here, the data about each of the tetra meshes
in the step S05 and the step S06 will be further
explained. Figs. 7A to 7C are diagrams showing that
10   the data of each of the tetra meshes in the steps S04
to S06. Sheets 21 to 23 show data in the steps S04 to
S06, respectively. In each sheet, Node is an
identification number which distinguishes each of the
plurality of tetra meshes in the FEM model, and σ, T,
15   σU and Saf are the stress, the temperature, the
normalized stress and the safety factor in each of the
tetra meshes, respectively (only the amplitude stress
is shown in Figs. 7A to 7C as the stress and the
normalized stress). The FEM analysis is accomplished
20   at the step S04 and the relationship between σ and T
every tetra mesh is obtained as shown by the sheet 21
shown in Fig. 7A. Next, the calculation (σU = f(σ,
T)) of the normalized stress is accomplished at the
step S05 by using the conversion functions f about
25   each data, and σU for each of the tetra meshes is
obtained as shown by the sheet 22 of Fig. 7B. Then,
the calculation (Saf = A/B) of the fatigue safety

factor is accomplished at step S06 and the fatigue

safety factor Saf for each of the tetra meshes is

obtained as shown by the sheet 23 Fig. 7C.

[061]   The stress data table 17 may store the

5 fatigue limit diagram for every temperature and every

material. In this case, however, an amount of data to

be stored increases more as the kind of the material

and the temperature increases more. As a result, the

system infrastructure becomes enormous and the access

10 time also increases.

[062]   On the other hand, in the present invention,

the stress data table 17 does not have data for every

temperature and every material and the normalized

fatigue limit function is calculated using the

15 conversion functions f. Therefore, the present

invention needs not to have a large-scale data and the

increase of the system can be restrained.

[063]   Also, in the present invention, the curve Q_0

of the normalized fatigue limit diagram has the

20 fatigue limit value of "1". Therefore, the fatigue

safety factor can be easily grasped numerically

through the comparison with the curve Q_0.

[064]   In this way, in the present invention, the

fatigue limit diagram which does not depend on the

25 temperature and the material is calculated by

normalizing the fatigue limit diagram which depends on

the temperature and material. Therefore, the data of

the stress can be easily treated.

[065]   By the present invention, the evaluation of
the fatigue safety factor of a part or unit using the
CAE calculation becomes possible in the design
5   conception step. Because the quality in the initial
design of the part or unit improves, faults in a
durable examination decrease largely and the cost can
be reduced in the design and the development.

[066]   According to the present invention, the
10   fatigue safety factor of each part can be calculated
at high speed and correctly through the automatic
process, and it is possible to improve the efficiency
of the design and development.